



## Mobilfluid 426

### Extra High Performance Multipurpose Tractor Fluid

#### Product Description

Mobilfluid 426 is an extra high performance multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. The advanced technology in Mobilfluid 426 is designed to optimise the performance of agricultural and commercial tractors operating in a wide range of environments and conditions. This next generation product combines select base oils and an advanced additive package to deliver the varied lubricant performance properties required by the drive trains of agricultural and construction equipment proven in severe duty applications. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter.

#### Features and Benefits

Next generation technology has vastly improved the performance capabilities of heavy-duty equipment in terms of load, speed, control, and reliability through innovative powertrain designs. These designs have changed and increased the requirements of powertrain fluids to deliver higher levels of performance and productivity while reducing operating costs. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and pumpability are features that must be optimally balanced to provide extended clutch life, maximum drawbar loading, and maintain operations on uneven terrain over a wide range of ambient temperatures. Mobilfluid 426 delivers exceptional performance in today's power train transmissions, drive axles, clutches, PTOs and hydraulic systems. The key benefits include:

Features	Advantages and Potential Benefits
Excellent frictional properties	Optimal clutch and PTO performance Excellent wet brake and PTO chatter control
Compatible with clutch materials and elastomers	Long clutch life and reduced leakage
High viscosity index and improved shear stability	Consistent operating response
Excellent protection against rust, corrosion, and yellow metal etching	Protects equipment in wet or humid environments and prevents premature wear
Excellent low temperature properties	Responsive operation and effective lubrication in cold weather applications
Strong anti-wear and extreme pressure properties	Reduces wear, extends equipment life, and reduces maintenance costs
Good thermal and oxidation stability	Reduces deposits, extends seal life, and increases service life of equipment and lubricant

Features	Advantages and Potential Benefits
Multipurpose capability	Simplifies inventory and reduces misapplication problems
Good filterability	Keeps systems clean and operating smoothly

## Applications

### Recommended by ExxonMobil for use in:

- Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs and hydrostatic drives
- Recommended in off-highway industries including: agriculture, construction, and quarrying
- Recommended for top-up and refill of systems
- Do not use in passenger car automatic transmissions
- Recommended by ExxonMobil for use in applications requiring API GL-4 grade lubricants in all gear applications except hypoid gear designs
- Potential replacement for engine oils recommended for hydraulic and transmission systems

## Specifications and Approvals

<b>Mobilfluid 426 has the following builder approvals:</b>	
Volvo WB 101	X
ZF-TE-ML 03E/05F/06K/17E	X

<b>Mobilfluid 426 meets or exceeds the requirements of:</b>	
Kubota UDT	X
Massey Ferguson MF M-1145	X

<b>Mobilfluid 426 is Recommended by ExxonMobil for use in applications requiring:</b>
API GL-4
AGCO Powerfluid 821 XL
Allison C-4 (Agriculture Applications Only)
Caterpillar TO-2
CNH MAT 3505, 3525
Denison HF-0, HF-1, HF-2 (T5D & P46 pumps only)
Ford New Holland FNHA-2-C-201.00
Ford ESN-M2C134-D
J. I. Case MS 1204-07/09
John Deere J20C
Vickers 35VQ25
Massey Ferguson MF M-1143, M-1141, M-1135

## Typical Properties

<b>Mobilfluid 426</b>	
Viscosity, ASTM D 445	
cSt @ 40°C	59
cSt @ 100°C	9.7
Brookfield Viscosity, cP (@ -20°C)	3800
Viscosity Index, ASTM D 2270	149
Pour Point, °C, ASTM D 97	-36
Flash Point, °C, ASTM D 92	228
Density @ 15°C kg/l, ASTM D 4052	0.889

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Toxicity class: free BAG T No.: 621000

The Mobil logotype, the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

1-2011

Esso Petroleum Company limited  
ExxonMobil House, Ermyrn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

[www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2012 Exxon Mobil Corporation. All rights reserved.