

SOUPLEX round belts

SOUPLEX brown



Hardness 85 ShA
Pretension 5 - 8%
Temperature range -20°C/+60°C
Friction coefficient HDPE : 0.35 Steel : 0.6 Stainless steel : 0.7
Roll length 30 m

Reference	Diameter (mm)	Traction force (daN)	Pretension	Pulley diameter (mm) recommended	mini
SXRM03	3	0.9	8%	20	15
SXRM04	4	1.5	8%	35	25
SXRM05	5	2.5	8%	40	30
SXRM06	6	4	8%	50	40
SXRM08	8	7	8%	70	55
SXRM9.5	9.5	10	8%	80	65
SXRM12.5	12.5	18	8%	110	95
SXRM15	15	25	8%	140	120
SXRM18	18	38	8%	200	150
*SXRM20	20	47	8%	240	190

*Manufactured on request depending on quantities.

SOUPLEX translucent




Reference	Diameter (mm)	Traction force (daN)	Pretension	Pulley diameter (mm) recommended	mini
SXRT03	3	0.9	8%	20	15
SXRT04	4	1.5	8%	35	25
SXRT05	5	2.5	8%	40	30
SXRT06	6	4	8%	50	40
SXRT08	8	7	8%	70	55

SOUPLEX black antistatic



Reference	Diameter (mm)	Traction force (daN)	Pretension	ø Pulley diameter (mm) recommended	mini
SXRN04AS	4	1.5	8%	45	35
SXRN05AS	5	2.5	8%	50	40
SXRN06AS	6	4	8%	60	50

tubular fastening belts



Fast on-site fastening without welding tools.

DEL/FLEX red tubular



Hardness 90 ShA
Pretension 3 - 6%
Temperature range -20°C/+70°C
Friction coefficient HDPE : 0.25 Steel : 0.5 Stainless steel : 0.6
Roll length 30 m

Reference	Diameter (D/d mm)	Traction force (daN)	Pretension	Pulley diameter (mm) recommended	mini
DFTR05	5/2.5	3	5%	60	50
DFTR06	6/2.5	5	5%	70	60
DFTR08	8/3	10	5%	90	70
DFTR10	10/4	16	5%	100	85
DFTR12	12/4	22	5%	140	125
DFTR15	15/5	35	5%	170	140
*DFTR18	18/5	50	5%	220	190

*Manufactured on request depending on quantities.

SOUPLEX brown tubular



Hardness 85 ShA
Pretension 5 - 8%
Temperature range -20°C/+60°C
Friction coefficient HDPE : 0.35 Steel : 0.6 Stainless steel : 0.7
Roll length 30 m

Reference	Diameter (D/d mm)	Traction force (daN)	Pretension	Pulley diameter (mm) recommended	mini
SXTM10	10/4	9	8%	80	70

Aluminium fasteners

N°	Belt dia.
4	5 & 6 mm
6	8 mm



N°	Belt dia.
7	10 & 12 mm
9	15 & 18 mm

Supplied in pack of 10.