

Hardness 85 ShA
Pretension 5 - 8%
Temperature range -20°C/+60°C
Friction coefficient HDPE : 0.35 Steel : 0.6 Stainless steel : 0.7
Roll length 30 m



solid

SOUPLEX brown




cogged

Reference	Traction force (daN)	Primitive pulley ø (mm) recommended	mini
SXVM08	4	50	40
SXVM10	6	70	55
SXVM13	12	80	70
SXVM17	22	130	110
SXVM22	36	170	130
SXVM32	71	250	220

Dimension (mm)	Pretension
8x5 (M)	8%
10x6 (Z)	8%
13x8 (A)	8%
17x11 (B)	8%
22x14 (C)	8%
32x19 (D)	8%

Reference	Traction force (daN)	Primitive pulley ø (mm) recommended	mini
-	-	-	-
SXVMCR10	4	50	40
SXVMCR13	8	60	50
SXVMCR17	15	90	70
SXVMCR22	25	130	110
SXVMCR32	50	180	150



solid

SUPERGRIP coating



cogged

Reference	Traction force (daN)	Primitive pulley ø (mm) recommended	mini
SXVM08NA	4	50	40
SXVM10NA	6	70	55
SXVM13NA	12	80	70
SXVM17NA	22	130	110
SXVM22NA	36	170	130
SXVM32NA	71	250	220

Dimension (mm)	Pretension
8x5 (M)	8%
10x6 (Z)	8%
13x8 (A)	8%
17x11 (B)	8%
22x14 (C)	8%
32x19 (D)	8%

Reference	Traction force (daN)	Primitive pulley ø (mm) recommended	mini
-	-	-	-
SXVMCR10NA	4	50	40
SXVMCR13NA	8	60	50
SXVMCR17NA	15	90	70
SXVMCR22NA	25	130	110
SXVMCR32NA	50	180	150

