



Datum diameter d _d (mm)	No. of grooves	Type	Type No.	Weight without bushing (≈kg)	Taper bushing	Datum diameter d _d (mm)	No. of grooves	Type	Type No.	Weight without bushing (≈kg)	Taper bushing
TB SPB/17						180	1		1	4.100	1610
100▲	1		1	0.900	1610		2		8	4.500	2517
	2		6	1.200	1610		3		2	5.500	2517
	3		6	1.700	1610		4		4	6.900	2517
112▲	1		1	1.100	1610		5		4	7.100	3020
	2		6	1.500	1610		6		4	7.700	3020
	3		6	2.000	1610		8		4	9.500	3020
118▲	1		1	1.300	1610	190	1		8	4.600	2012
	2		6	1.700	1610		2		8	5.000	2517
	3		6	2.300	1610		3		2	6.300	2517
125▲	1		1	1.500	1610		4		4	7.600	2517
	2		2	1.900	2012		5		4	8.100	3020
	3		2	2.400	2012		6		4	9.200	3020
	4		4	3.000	2012		8		4	11.200	3030
	5		6	3.500	2012	200	1		8	5.000	2012
132▲	1		1	1.800	1610		2		8	5.400	2517
	2		2	2.200	2012		3		2	6.500	2517
	3		2	2.800	2012		4		2	8.800	3020
	4		4	3.400	2012		5		2	9.100	3020
	5		4	3.700	2012		6		4	10.300	3020
140	1		1	2.300	1610		8		4	13.500	3535
	2		2	2.700	2012	212	1		8	4.200	2012
	3		2	3.300	2012		2		8	4.900	2517
	4		2	3.700	2517		3		2	6.000	2517
	5		2	4.500	2517		4		2	9.800	3020
	6		4	4.600	2517		5		2	11.000	3020
150	1		1	2.700	1610		6		4	14.300	3535
	2		2	3.100	2012		8		4	16.600	3535
	3		2	3.900	2517	224	1		8	4.700	2012
	4		2	4.400	2517		2		8	5.300	2517
	5		4	5.200	2517		3		2	6.300	2517
	6		4	5.600	2517		4		2	11.300	3020
160	1		1	2.500	1610		5		2	12.700	3020
	2		2	2.900	2012		6		4	17.000	3535
	3		2	4.200	2517		8		4	19.300	3535
	4		4	4.900	2517		10		4	21.800	3535
	5		4	6.000	2517	236	1		8	5.000	2012
	6		4	5.400	3020		2		8	5.500	2517
170	1		1	2.900	1610		3	x	10	7.000	2517
	2		2	3.300	2012		4	x	10	14.500	3020
	3		2	4.900	2517		5		6	16.900	3535
	4		4	5.700	2517		6		4	20.000	3535
	5		4	6.100	3020		8		4	22.300	3535
	6		4	6.500	3020		10		4	25.300	3535
	8		4	8.000	3020						



optibelt KS V-Grooved Pulleys for Taper Bushings Profile SPB

Datum diameter d _d (mm)	No. of grooves	Type	Type No.	Weight without bushing (≈kg)	Taper bushing	Datum diameter d _d (mm)	No. of grooves	Type	Type No.	Weight without bushing (≈kg)	Taper bushing
250	1	☐	8	5.400	2012	375	2	x	7	9.500	3020
	2	x	7	5.500	2517		3	x	10	11.500	3020
	3	☐	2	7.700	3020		4	x	10	16.500	3525
	4	☐	2	19.600	3020		6	x	10	25.000	3535
	5	☐	4	21.700	3535		8	x	10	28.000	4040
	6	☐	4	23.300	3535	400	2	x	7	10.000	3020
	8	☐	4	27.500	3535		3	x	7	18.300	3535
	10	☐	4	29.300	3535		4	x	7	20.500	3535
265	2	☐	7	6.200	2517		5	x	10	23.400	3535
	3	☐	9	8.000	3020		6	x	10	25.100	3535
	4	☐	9	9.500	3020		8	x	10	36.500	4040
	6	☐	9	16.700	3525		10*	x	10	41.000	4040
	8	☐	9	24.000	3525	425	2	x	7	11.500	3020
280	1	x	7	6.100	2012		3	x	7	18.000	3535
	2	x	7	6.800	2517		4	x	7	19.500	3535
	3	x	10	8.600	3020		6	x	10	25.100	4040
	4	☐	9	10.100	3020		8	x	10	52.500	4545
	5	☐	9	17.800	3535	450	2	x	7	12.100	3020
	6	☐	9	19.600	3535		3	x	7	21.900	3535
	8	☐	9	26.700	3535		4	x	7	24.500	3535
	10	☐	9	30.500	3535		5	x	10	27.300	3535
300	2	x	7	7.300	2517		6	x	10	35.500	4040
	3	x	10	9.200	3020		8	x	10	40.900	4040
	4	☐	9	14.300	3020		10*	x	10	53.500	4545
	5	☐	9	18.200	3535	500	2	x	7	13.200	3020
	6	☐	9	21.900	3535		3	x	7	23.100	3535
	8	☐	9	26.200	3535		4	x	7	26.600	3535
315	1	x	7	7.200	2012		5	x	10	29.900	3535
	2	x	7	7.800	2517		6	x	10	38.900	4040
	3	x	10	9.600	3020		8	x	10	45.500	4040
	4	☐	5	17.100	3535		10*	x	10	61.000	4545
	5	☐	9	18.800	3535	560	2	x	7	16.500	3030
	6	☐	9	23.000	3535		3	x	7	25.900	3535
	8	☐	9	26.000	3535		4	x	7	29.000	3535
	10	☐	9	31.500	3535		5	x	7	35.300	4040
335	2	x	7	7.800	2517		6	x	10	43.100	4040
	3	x	10	10.500	3020		8	x	10	49.000	4545
	4	x	7	18.300	3535		10*	x	10	55.700	4545
	5	x	10	19.500	3535	630	2	x	7	18.500	3020
	6	x	10	22.000	3535		3	x	7	28.900	3535
	8	x	10	28.200	3535		4	x	7	33.300	3535
	10*	x	10	36.000	4040		5	x	7	43.100	4040
							6	x	10	49.200	4040
355	2	x	7	8.700	3020		8	x	10	62.000	4545
	3	x	10	10.800	3020	710	10*	x	10	72.000	4545
	4	x	7	18.600	3535		3	x	7	33.200	3535
	5	x	10	20.800	3535		4	x	7	39.100	3535
	6	☐	9	22.800	3535		5	x	7	50.200	4040
	8	x	10	27.000	3535		6	x	10	62.300	4545
	10*	x	10	38.000	4040		8	x	10	71.000	4545
							10*	x	10	80.000	4545



Datum diameter d _d (mm)	No. of grooves	Type	Type No.	Weight without bushing (≈kg)	Taper bushing	Datum diameter d _d (mm)	No. of grooves	Type	Type No.	Weight without bushing (≈kg)	Taper bushing	
800	3	x	7	36.700	3535							
	4	x	7	48.800	4040							
	5	x	7	56.100	4040							
	6	x	10	71.400	4545							
	8	x	10	90.900	4545							
	10*	x	10	102.000	4545							
900	3	x	7	46.800	3535							
	4	x	7	60.000	4040							
	5	x	7	74.800	4545							
	6	x	10	81.500	4545							
	8	x	10	110.000	4545							
	10*	x	10	126.000	5050							
1000	3	x	7	56.500	4040							
	4	x	7	66.500	4040							
	5	x	7	80.500	4545							
	6	x	10	90.000	4545							
	8	x	10	132.000	5050							
	10*	x	10	147.000	5050							
									</			