

Datum diameter d_d (mm)	No. of grooves	Type	Weight (≈kg)	Finished bore hole d_{max} (mm)	Hub length l (mm)	Datum diameter d_d (mm)	No. of grooves	Type	Weight (≈kg)	Finished bore hole d_{max} (mm)	Hub length l (mm)
SPZ/10						140	1	☐	0.900	28	24
45▲	1	☐	0.200	16	24		2	☐	1.400	38	38
	2	☐	0.300	16	35		3	☐	1.700	38	40
50▲	3	☐	0.400	16	35	150	1	x	1.100	28	24
	1	☐	0.300	20	24		2	☐	1.500	38	38
	2	☐	0.400	20	35		3	☐	1.900	38	40
56▲	3	☐	0.500	20	40	160	1	x	1.200	32	30
	1	☐	0.300	20	24		2	x	1.600	38	38
	2	☐	0.500	25	35		3	x	2.400	42	40
63	3	☐	0.700	25	40	170	1	x	1.700	40	30
	1	☐	0.300	25	24		2	x	1.900	40	38
	2	☐	0.600	25	35		3	x	3.000	42	40
71	3	☐	0.900	25	40	180	1	x	2.100	32	30
	1	☐	0.300	25	24		2	x	3.100	38	38
	2	☐	0.600	25	35		3	x	3.500	42	40
75	3	☐	1.000	30	40	190	1	x	2.300	35	30
	1	☐	0.400	24	24		2	x	2.400	35	38
	2	☐	0.600	24	35		3	x	4.000	35	40
80	3	☐	1.100	28	40	200	1	x	2.400	32	38
	1	☐	0.400	25	24		2	x	2.900	38	38
	2	☐	0.700	30	35		3	x	4.500	42	40
85	3	☐	1.100	38	35	212	1	x	2.600	35	30
	1	☐	0.300	25	24		2	x	3.400	35	38
	2	☐	0.700	30	35		3	x	5.000	38	40
90	3	☐	1.100	38	35	225	1	x	2.800	32	38
	1	☐	0.400	25	24		2	x	4.000	38	38
	2	☐	0.800	30	35		3	x	5.300	42	40
95	3	☐	1.200	38	38	250	1	x	3.300	32	38
	1	☐	0.400	28	24		2	x	4.800	38	38
	2	☐	0.800	28	35		3	x	6.000	42	40
100	3	☐	1.200	38	38	280	1	x	3.900	35	34
	1	☐	0.500	28	24		2	x	5.200	42	38
	2	☐	0.900	30	35		3	x	7.000	48	40
106	3	☐	1.300	38	38	315	1	x	4.400	35	34
	1	☐	0.500	30	24		2	x	6.800	42	38
	2	☐	1.000	28	35		3	x	8.300	48	40
112	3	☐	1.300	38	38	355	1	x	4.600	35	34
	1	☐	0.500	28	24		2	x	8.000	42	40
	2	☐	1.000	30	35		3	x	10.000	48	45
118	3	☐	1.400	38	38						
	1	☐	0.600	28	24						
	2	☐	1.100	38	35						
125	3	☐	1.500	38	38						
	1	☐	0.700	28	24						
	2	☐	1.200	38	35						
132	3	☐	1.600	38	40						
	1	☐	0.800	30	24						
	2	☐	1.300	38	35						
	3	☐	1.600	40	40						

No. of grooves z	1	2	3
Face width b_2 (mm)	16	28	40

● Solid pulley ○ Plate pulley (with or without holes) x Spoked pulley
 ▲ only for profile 10
 Hub position: one side flush
 Material: EN-GJL 200 - DIN EN 1561